

**Все инструменты**

+7 (495) 730-35-00

8 800 550-37-70

Free call 05:00 – 22:00

Check order status

Pay for the order online

[Login](#) | [Registration](#)

Catalog

Search among 500 thousand products. Enter a request



Basket

Home / Building materials / Construction chemicals / Sealant / Tytan

## Rubber sealant for roofing TYTAN PROFESSIONAL colorless 310ml 91455

Product code: 15897345

2 reviews | 1 question

To favorites

Compare

Manufacturer's warranty does not cover



Not available



Last price

**659 r.**

[Find an analogue](#)

[Learn about admission](#)

DESCRIPTION AND CHARACTERISTICS

REVIEWS 2

EXPENDABLE MATERIALS

QUESTIONS 1

SERVICE

Rubber sealant for roofing TYTAN PROFESSIONAL colorless 310ml 91455 - an elastic sealant based on synthetic rubber designed for the reconstruction and repair of expansion joints and joints on roofs.

The available colors of the sealant provide an aesthetic appearance of the joint.

The product has excellent adhesion without the use of a primer to most roofing materials:

- bitumen roof
- resin for roofs
- shingles
- brick
- stone
- concrete
- wood
- metal

### Manufacturer



Poland is the birthplace of the brand

Poland - country of production

### Packing Information

Product unit: piece

Weight, kg: 0.38

Length, mm: 50

Width, mm: 50



Online chat

## BENEFITS

- High elasticity/flexibility that does not decrease over time
- Waterproof connection
- Can be dyed
- Excellent adhesion without priming
- High weather and UV resistance
- Resistant to mold and mildew
- Can be stored at -30°C for up to 2 weeks
- Withstands 4 freeze cycles
- Base: synthetic rubber
- Creates an elastic flexible seam
- Possibility of dyeing: yes
- Suitable for wet surfaces
- Durability: up to 20 years

## Specifications

Sealant type .....	rubber
Volume, l .....	0.31
Net weight, kg .....	0.38
Purpose .....	for roofing
Properties .....	highly elastic
Type of container .....	cartridge
Max application temperature, °C .....	+40
Min application temperature, °C .....	+5
Max operating temperature, °C .....	+100
Min operating temperature, °C .....	-25
Curing conditions .....	air humidity
Number of components .....	one
Consistency .....	paste
Bonded materials .....	metal, PVC
Glue base .....	rubber
Color .....	transparent
frost-resistant .....	Yes

## Advantages

For various types of roof tiles, aprons, metal and PVC drains, drain pipes  
TYTAN PROFESSIONAL 91455 has excellent adhesion to most roofing materials.

Base: synthetic rubber

Skin formation time: 2-15 min

Application temperature 5 °C to 40 °C

Temperature resistance from -25 °C to 100 °C

Modulus at 100% elongation: 0.20-0.25 N/mm<sup>2</sup>

Shelf life: 24 months


Modulus at 100% elongation: 0.20-0.25 N/mm<sup>2</sup>

Shelf life: 24 months




**Manufacturer's warranty does not cover**  
for Tytan products


*\* The manufacturer reserves the right to change the characteristics, appearance, configuration of the product and the place of its production without notifying the dealer. This information is not a public offer*

 Found an error in the characteristics or description?

## Documentation

 User manual

 Certificates of conformity

 Download all documentation



Online chat