

WORKING VOLTAGE : 27.5/√3 kV 50/60 Hz
 TEST VOLTAGE : 65 kV 50 Hz 72 s ou 130 kV DC 72 s
 FULL LIGHTING IMPULSE : 125 kV 1.2/50 us
 PARTIAL DISCHARGE : ≤ 10 pC at 27.5 kV 50 Hz
 TEMPERATURE RANGE : -25°C +90°C
 WEIGHT : ~ 20 kg

TYPE	CAPACITANCE [nF]	Tol [%]	ΔC/C	TAN δ 10 ⁻⁴ AT UN
CDOR2219B11	100	±5	-0.2%/°C	20



EXECUTION :

- 1) OIL FILLED MIXED DIELECTRIC CAPACITOR (PAPER AND SYNTHETIC FILM)
- 2) OIL AND GAZ TIGHT
- 3) JOINTS ARE OIL AND OZONE RESISTANT
- 4) WORKING POSITION , HORIZONTAL, VERTICAL OR INCLINED
- 5) EPOXY RESIN INSULATOR

Abgabe an Drittpersonen sowie Reproduktion, auch nur teilweise, verboten sofern von der Gesellschaft genehmigt.
 Remise à des tiers, ainsi que reproduction, même partielle, interdites sauf autorisation écrite de la société.
 Disposal to third persons or reproduction, even in part, prohibited without written authority from the company.

Alle Rechte vorbehalten
 Tous droits réservés
 All rights reserved

© 2019 CONDIS SA

Remplace:				Remplace par:				 			
Modif.	02	01.05.19	DLA					Echelle	Dessine	05.10.07	DJF
	01	31.03.16	GOJ					Contrôle	01.05.19	DLA	
	00A	23.07.13	DJF					Réf.			
CONDIS®				COUPLING CAPACITOR				Y028H3100A360B11			