



Another city


161 stores

Receipt and payment

Service and Support

Companies

Contacts



+7 (495) 730-35-00

8 800 550-37-70

Free call 05:00 – 22:00

Check order status

Pay for the order online

Login | Registration

Catalog

Search among 500 thousand products. Enter a request



Basket

Home / Building materials / Construction chemicals / Sealant / Tytan

Rubber sealant for roofing TYTAN PROFESSIONAL brown 310ml 91691

Product code: 15897339

2 reviews | 1 question

To favorites

Compare

Manufacturer's warranty does not cover



Best price

Below average market



599 r.

Add to cart

Quick order



Buy by package

Price per pack of 6 pcs.: 3 282 rubles.

Price per one. goods: 547 p. 599 r.



Write off up to 240 rubles.

bonuses We will accrue 5

bonuses

Found cheaper? Report!



Pickup: September 22, after 08:00, in 154 stores



By courier: September 22, from 190 rubles.

DESCRIPTION AND CHARACTERISTICS

REVIEWS 2

EXPENDABLE MATERIALS

QUESTIONS 1

HOW TO GET

SERVICE

Rubber sealant for roofing TYTAN PROFESSIONAL brown 310ml 91691 - an elastic sealant based on synthetic rubber designed for the reconstruction and repair of expansion joints and joints on roofs.

The available colors of the sealant provide an aesthetic appearance of the joint.

The product has excellent adhesion without the use of a primer to most roofing materials:

- bitumen roof
- resin for roofs
- shingles
- brick
- stone
- concrete

Manufacturer



Poland is the birthplace of the brand

Poland - country of production



Packing Information

Product unit: piece

Online chat

- wood
- metal


Weight, kg: 0.38
 Length, mm: 50
 Width, mm: 50
 Height, mm: 230

BENEFITS

- High elasticity/flexibility that does not decrease over time
- Waterproof connection
- Can be dyed
- Excellent adhesion without priming
- High weather and UV resistance
- Resistant to mold and mildew
- Can be stored at -30°C for up to 2 weeks
- Withstands 4 freeze cycles
- Base: synthetic rubber
- Creates an elastic flexible seam
- Possibility of dyeing: yes
- Suitable for wet surfaces
- Durability: up to 20 years

Documentation

 Certificates of conformity

 Download all documentation

Specifications

Sealant type	rubber
Volume, l	0.31
Net weight, kg	0.38
Purpose	for roofing
Properties	paintable
Type of container	cartridge
Max application temperature, °C	+40
Min application temperature, °C	+5
Max operating temperature, °C	+100
Min operating temperature, °C	-25
Curing conditions	solvent evaporation
Number of components	one
Consistency	paste
Bonded materials	metal, PVC
Glue base	rubber
Color	brown
frost-resistant	yes

Advantages

For various types of roof tiles, aprons, metal and PVC drains, drain pipes
 TYTAN PROFESSIONAL 91691 has excellent adhesion to most roofing materials.

Base: synthetic rubber

Skin formation time: 2-15 min

Application temperature 5 °C to 40 °C

Temperature resistance from -25 °C to 100 °C

Deformation mobility: 25?%

Curing time: 1-2 mm?/?days

Modulus at 100% elongation: 0.20-0.25 N/mm²

Shelf life: 24 months



Manufacturer's warranty does not cover
 for Tytan products

** The manufacturer reserves the right to change the characteristics, appearance, configuration of the product and the place of its production without notifying the dealer. This information is not a public offer*



Online chat